

## **CLAIMS**

The following is a complete listing of claims with a status identifier in parenthesis.

### **LISTING OF CLAIMS**

1. (Original) A method of determining a time offset estimate between a central node and a secondary node, comprising:  
receiving, at a central node, downlink and uplink timing information from a secondary node, the downlink and uplink timing information based on a periodic timing scale, the downlink timing information representing timing information for communication from the central node to the secondary node and the uplink information representing timing information for communication from the secondary node to the central node;  
converting the received downlink and uplink timing information to a continuous time scale; and  
determining a time offset estimate between the central node and the secondary node based on the converted downlink and uplink timing information.
2. (Original) The method of claim 1, wherein the downlink information includes a first time measured at the central node of sending a downlink frame to the secondary node and a second time measured at the secondary node of receiving the downlink frame, and the uplink information includes a third time measured at the secondary node of sending an uplink frame.

3. (Original) The method of claim 2, further comprising:  
measuring, at the central node, a fourth time of receiving the uplink  
frame; and wherein  
the converting step converts the first, second, third and fourth times to a  
continuous time scale.

4. (Original) The method of claim 3, wherein the determining step  
comprises:  
determining uplink and downlink delay indicators based on the  
converted first, second, third and fourth times; and  
calculating the time offset estimate based on the uplink and downlink  
delay indicators.

5. (Original) The method of claim 4, wherein  
the determining uplink and downlink delay indicators step is performed  
for a plurality of first, second, third and fourth time sets; and  
the calculating step calculates the time offset estimate based on the  
plurality of uplink and downlink delay indicators.

6. (Original) The method of claim 5, wherein the calculating step  
comprises:  
determining a minimum uplink delay indicator and a minimum downlink  
delay indicator from the plurality of uplink and downlink delay indicators; and  
calculating the time offset estimate based on the minimum downlink  
delay indicator and the minimum uplink delay indicator.

7. (Original) The method of claim 1, further comprising:  
sending a downlink frame to the secondary node, the downlink frame including a first time measured at the central node indicating when the downlink frame is sent; and wherein  
the receiving step receives an uplink frame at the central node, the uplink frame includes the first time, a second time measured at the secondary node of receiving the downlink frame, a third time measured at the secondary node of sending the uplink frame.

8. (Original) The method of claim 1, further comprising:  
setting a timer at a start of the method; and  
stopping the method if the timer times out.

9. (Original) The method of claim 1, further comprising:  
compensating the time offset estimate for DC bias errors.

10. (Original) The method of claim 1, wherein the central node is a radio network controller.

11. (Original) A method of determining a time offset estimate between a central node and a secondary node, comprising:  
receiving, at a central node, downlink and uplink timing information from a secondary node, the downlink and uplink timing information based on a periodic timing scale, the downlink timing information representing timing information for communication from the central node to the secondary node and the uplink information representing timing information for communication from the secondary node to the central node;

adjusting the received downlink and uplink timing information for time wraparound; and

determining a time offset estimate between the central node and the secondary node based on the adjusted downlink and uplink timing information.